

# Flails

Model	Cutting Width (mm)	Number of Hammers	Number of Blades	Cuts Material (mm)	Required Oil Flow (lpm)	Working Pressure (bar)	Working Weight (kg)	Excavator Weight Class (t)
GREEN/SB60	600	10	20	10-20	25-30	195-205	100	1.5-2
GREEN/SB80	800	14	28	10-20	25-30	195-205	110	1.5-2
NKR/SB60	550	-	20	15-20	33-37	195-205	150	2-4
NKR/SB80	750	-	28	15-20	33-37	195-205	170	2-4
NKR/SB100	950	-	36	15-20	38-42	195-205	190	2-4
GKR/SB60	540	8	-	20-30	33-37	195-205	185	2.5-4
GKR/SB80	740	12	-	20-30	38-42	195-205	215	2.5-4
CKT/SB80	710	12	36	40	43-47	195-205	260	4.5-5.5
CKT/SB100	910	16	48	40	43-47	195-205	290	4.5-5.5
PARK/SB90	820	12	36	50	63-67	215-225	415	6-8
PARK/SB110	1020	16	48	50	63-67	215-255	455	6-8
RA/SB95	890	8	24	60	78-82	215-225	405	7.5-9
RA/SB115	1090	10	30	60	78-82	215-225	450	7.5-9
RA/SB125	1190	12	36	60	78-82	215-225	475	7.5-9
LAND/SB 160	1490	16	32	100-120	105-115	275	970	12-20
LAND/SB 200	1890	20	40	100-120	130	275	1080	12-20

## Product features

- A** Self-levelling support (up to PARK SB model)  
All models with under plate for mounting bracket
- B** Purpose made mounting hitch
- C** Removable front inspection hood
- D** High Quality Goodyear Drive Belts
- E** Levelling roller
- F** Side skids
- G** Enclosed and protected Drive Belts on applicable models

