

Rotary Screening Buckets

	PSB 030R	PSB 040R	PSB 050R	PSB 100R	PSB 120R	PSB 200R	PSB 250R	PSB 300R	PSB 500R
Weight (kg)	110	250	350	860	1540	1570	2440	2550	4900
Overall Depth (mm)	740	1070	1175	1450	1730	2190	2080	2600	2950
Overall Height (mm)	630	805	930	1170	1500	1650	1900	2000	2410
Basket Width C (mm)	320	445	515	695	805	925	985	1040	1360
Basket External Diameter D (mm)	500	640	750	900	1170	1340	1560	1700	2000
Inlet Width (mm)	520	700	800	1100	1440	1400	1900	1750	2120
Working Capacity (m3)	0.08	0.2	0.3	0.4	0.75	0.9	1.1	1.5	2.7
Max Working Pressure (bar)	120	120	120	120	220	220	220	220	220
Max Oil Flow (l/min)	30	50	50	60	80	80	80	80	80
Drum Speed (rpm)	24/32	18/24	18/24	18/24	18/35	18/35	18/35	18/35	18/27
Excavator Weight Class (t)	1.4-2.8	2.5-5.5	4.5-9	7-14	12-18	16-23	21-33	30-45	40-65

Features **PATENTED 4-piece interchangeable screen kit - 20 - 150mm available**

Product features

- A** Integrated high pressure relief valve
- B** Drum protection casing
- C** Heavy duty double bearing slew ring
- D** PATENTED 4-piece interchangeable screens - 20-150mm
- E** Exclusive wide inlet profile
- F** Bolt-on wear edges



PRODEM.