



OilQuick Coupler

	OQ 40/24	OQ 45-5	OQ 60-5	OQ 65	OQ 70/55	OQ 80	OQ 90	OQ 120
Width (mm)	240	290	340	440	550	590	750	870
Pin distance (mm)	300	430	480	530	600	670	750	925
Weight (kg)	32	85	135	170	230	320	630	1200
Max. number of hose couplings								
Max.	4	5	5	5	6	6	9	8
3/8"	2	3	2	-	-	-	1	-
1/2"	2	2	1	2	2	2	3	3
3/4"	-	-	2	3	2	2	1	-
1"	-	-	-	-	2	2	4	3
1,5"	-	-	-	-	-	-	-	2
Electrical coupling (option)	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Excavator Weight Class (t)	1-5	5-12	8-18	14-22	18-28	25-40	40-70	70-120

Attachment Adapters



Mechanical attachment adapter



Hydraulic attachment adapter



Hydraulic Bolt-on-adapter



Pendulum adapter for attachments

Product features

- A** Change attachments in ten seconds!
- B** No external hoses to attachments
- C** Twin lock with OilQuick lock support
- D** Enables the right attachment for the job
- E** Maximum of up to 9 couplings
- F** No oil loss during change over